

LEXUS RX (2019/10-) (AGL2#W/GYL2#W) Daylight KIT

SET UP GUIDE

1. Please refer to Figure 1 and Figure 1-A . Attachment B has a specific installation direction. Install it so that the light-emitting surface is facing the inside of the vehicle and the wiring is facing downwards.
2. Thoroughly degrease the grooves of the garnish.
3. Peel off the release paper from the double-sided tape of accessory B , insert part A in Figure 1 into part A in Figure 2, and part B in Figure 1 into part B in Figure 2, and attach accessory B to the groove in the garnish.
4. Remove the original bumper.
5. Temporarily assemble the garnish onto the genuine bumper and mark the installation position with masking tape or similar.
6. Drill a 5.0mm hole in the part shown in Figure 2  (where the back of the garnish touches, the garnish is thick enough that the screw will not penetrate). Drill a 5.0mm hole in the factory bumper to pass the wiring through the part hidden by the garnish in Figure 2. 
7. Once again, temporarily assemble the garnish to the genuine bumper, mark the hole made in step 6 on the garnish, and drill a 3.2mm hole in the marked location.
8. Thoroughly degrease the garnish mounting area, and apply the included product c to the area shown in Figure 2.
9. Please read the attached sheet carefully for advice on using the sealer before installing the garnish to the genuine bumper.
10. In the part shown in Figure 2  secure the part from the inside of the genuine bumper towards the garnish using accessory A.
11. Install the original bumper onto the vehicle.

The left and right sides are installed in the same way.

List of included parts;	quantity
A: 4x12 tapping screws	8
B: Line LED	1
C: Solar sealant.	1

