

LEXUS RX F SPORT
(TALA15/TALH17)
2022/11-
Daylight KIT

Set up Guide

1. Thoroughly degrease the LED mounting groove area on the garnish surface.
2. Remove the release paper from the double-sided tape included in part B, insert part A in figure 1 into part A in figure 2, and part B in figure 1 into part B in figure 2, and then attach part b to the groove of the garnish.
3. Remove the original bumper.
4. Temporarily attach the garnish to the original bumper and mark the mounting position with masking tape or similar.
5. Drill a 5.0mm hole in the area shown in figure 3 ● (where the back shape of the garnish makes contact, where the garnish is thick and the screw cannot penetrate). Drill another 5.0mm hole in the original bumper in the area hidden by the garnish in ● figure 3 to pass the wiring through.
6. Once again, temporarily attach the garnish to the original bumper, mark the garnish through the hole you drilled in step 5, and drill a 3.2mm hole at the marked location.
7. Thoroughly degrease the mounting area on the back of the garnish, and apply the included product C to the area shown in figure 3.
8. In figure 3 ● , secure the part from the inside of the genuine bumper towards the garnish using the included part A.
9. Please install the original bumper onto the vehicle.

For wiring, connect the red wire to a wire with a 12V output when the ignition is ON, and the black wire to the body ground. (Connect from an accessory socket inside the vehicle.)

➤ The installation process is the same for both the left and right sides.

List of included parts:	quantity
A.4x12 tapping screws	6
B. Line LED(dl-31)	2
C. Sealant	1

