TESLA Model Y
(YL1YT)
2025/3-
Rear Gate Spoiler

Set up Guide

EXCLUSIVE ZEUS

■ This product is made of ABS/AES

■ This guide explains how to install the M'z SPEED product on the vehicle .for safe and proper installation,please read this guide carefully before starting the work.

Installation Procedure

1. Refer to **Figure 2**, temporarily place the product on the vehicle, check the clearance and overall balance, and mark the installation position with masking tape as needed.
2. As shown in the product rear view, slightly peel back the release liner of the double-sided tape on the product, fold it outward, and temporarily fix the product to the vehicle. Then remove the release liner little by little and press firmly.
3. Align the product with the markings, and while slowly removing the release liner, press the double-sided tape firmly to the vehicle surface to ensure a secure installation.

Included Parts List

	Item	Part Name	Quantity
Included Parts			

Fig. 1

Rear View of Product



= Double-Sided Tape

Fig. 2



■ Cautions

※ After unpacking, please check that all accessories are present and undamaged.
※ This product is made of ABS / AES molded plastic. Applying excessive force may cause damage, so please do not do so. Please note that damage caused by such force will not be covered under warranty.
※ This product may require some modification due to vehicle and product tolerances, so please be sure to check the installation compatibility. Please protect the vehicle and product with tape to prevent scratches, etc.
※ Please be aware that we cannot accept any responsibility for malfunctions or accidents caused by improper processing, assembly, or misuse of this product.
※ After installing this product, do not subject it to impact or get it wet (e.g., car washing) for 24 hours.
※ The bolts and screws used to attach various parts may loosen over time, so please check them occasionally.
※ We cannot accept returns after installation.

■ Important Notes Before Painting

※ Always perform a fitting check before painting.
※ Due to the manufacturing process, burrs and voids may inevitably occur in the product. Please remove them during the painting and surface preparation stage.
※ Please be sure to use urethane-based paint specifically for dry resins. Also, please allow the painting may at room temperature. Heat drying may cause warping or deformation the Furtherwork. please understand that we cannot accept any claims regarding the paintwork.
※ We cannot accept returns after painting or installation.

M'z SPEED
M'z SPEED Co., Ltd.
3-8-7 Shinkitajima, Higashiosaka City, Osaka 578-0966, Japan
Email : randi@mzspeed.co.jp
WA : +81 80-7675-5646